



Submarine Manufacturing & Products Limited

+44 (0)1772 687775 info@smp-ltd.co.uk www.smp-ltd.com
Blackpool Road, Newton, Preston, Lancashire, United Kingdom PR4 3RE

PRODUCT DATASHEET

Amron Amcom II 2-Diver Deluxe Portable Rechargeable Communicator with External Charger



THIS PRODUCT HAS THE FOLLOWING OPTIONS:

No product options are available.

OVERVIEW

The Amron International Amcom II 2-Diver Deluxe Portable Rechargeable Communicator with External Charger is the most versatile and powerful two diver communicator on the market today. The most unique feature is the design of separate channels and volume controls for each diver and the tender, both for the uplink and the downlink paths.



Submarine Manufacturing & Products Limited

+44 (0)1772 687775 info@smp-ltd.co.uk www.smp-ltd.com
Blackpool Road, Newton, Preston, Lancashire, United Kingdom PR4 3RE

DESCRIPTION

The Amron International Amcom II 2-Diver Deluxe Portable Rechargeable Communicator with External Charger is the most versatile and powerful two diver communicator on the market today. The most unique feature is the design of separate channels and volume controls for each diver and the tender, both for the uplink and the downlink paths. Each diver may have different equipment such as microphones and speakers or different listening and speaking characteristics. You can set the volume for each diver and tender to their individual comfort level. Both divers can be set up on 2-wire and/or 4-wire mode, or one diver on 4-wire mode and the other on 2-wire mode or any combination of the two modes.

FEATURES

Volume Control: Volume setting for each diver and tender to their individual comfort level

Wiring Modes: Both divers can be set up on 4-Wire Mode or 2-Wire Mode or any combination of the two modes

Microphone Adjustment: Ability to use both dynamic and pre-amplified diver microphones with a unique circuit that detects microphone type and automatically adjusts volume levels

Weatherproof: Weatherproof panel microphone for greater voice intelligibility

System Charge: Communicator can be left on charge indefinitely without damage to the batteries or communicator (/23 and /24 versions only). Communicator can be operated directly from the charger where AC power is available (/23 and /24 versions only)

SPECIFICATION

Audio Power Output: 22 Watts per channel

Frequency Response: 300Hz to 12kHz

Isolation Transformer: Split Bobbin Medical Grade

Height: 10in (25.4cm)

Width: 9in (22.9cm)

Length: 14.5in (36.8cm)



Submarine Manufacturing & Products Limited



+44 (0)1772 687775



info@smp-ltd.co.uk



www.smp-ltd.com

Blackpool Road, Newton, Preston, Lancashire, United Kingdom PR4 3RE

Weight: 22.5 lbs (10.2 kg)

Power: 110/220VAC 50/60 Hz (automatic sensing), or Internal/External Batteries 12VDC (/23 and /24 versions only)

ORDER THIS PRODUCT

To order this product or to request a price contact our UK sales team on

+44 (0)1772 687775

Alternatively you can place a quote request through our website

<http://www.smp-ltd.co.uk/> or send an email to sales@smp-ltd.co.uk