



Submarine Manufacturing & Products Limited

+44 (0)1772 687775 info@smp-ltd.co.uk www.smp-ltd.com
Blackpool Road, Newton, Preston, Lancashire, United Kingdom PR4 3RE

PRODUCT DATASHEET

Amron Amcom II 2-Diver Rack Mount Communicator



THIS PRODUCT HAS THE FOLLOWING OPTIONS:

No product options are available.

OVERVIEW

Amron's line of Rack Mount Communicators are the most versatile and powerful communicators on the market today.Â



Submarine Manufacturing & Products Limited

+44 (0)1772 687775 info@smp-ltd.co.uk www.smp-ltd.com
Blackpool Road, Newton, Preston, Lancashire, United Kingdom PR4 3RE

DESCRIPTION

Amron's line of Rack Mount Communicators are the most versatile and powerful communicators on the market today. The most unique feature is the design of separate channels and volume controls for each diver and the tender, both for the up-link and the down-link paths. You can set the volume for each diver and tender to their individual comfort level. Both divers can be set up on 4-Wire or 2-Wire mode, or one diver on 4-Wire and the other diver on 2-Wire mode, or any combination of the two modes. Comes standard with rear mounted MS connector, providing connections to diver and tender inputs and outputs. All rack mount radios include a hand-held, push-to-talk microphone.

FEATURES

- Volume setting for each diver and tender to their individual comfort level
- Divers can be set up on 4-Wire Mode or 2-Wire Mode or any combination of the two modes
- Ability to use both dynamic and preamplified diver microphones with a unique circuit that detects microphone type and automatically adjusts volume levels
- Weatherproof panel microphone for greater voice intelligibility
- Battery Condition Indicator - Visual LED indicator of battery condition
- Communicator can be left on charge indefinitely without damage to the batteries or communicator
- Communicator can be operated directly from the charger where AC power is available

SPECIFICATION

- Power** - 110/220VAC, 50/60Hz (automatic) with 2 internal batteries, 12VDC
- Audio power output** - 20 watts per channel
- Frequency response** - 300Hz to 12kHz
- Rear connector input/output** - 20 pin female MS
- Enclosure** - 19 in. rack, aluminum, black anodized
- Back-up Battery** - 2 ea. 6VDC rechargeable spring top Gel-Cell Batteries (Part No. 2890-04)
- Battery Life** - 20 hours (approx.)
- Height** - 7 in. (17.8 cm.)
- Width** - 19 in. (48.3 cm.)
- Depth** - 13 in. (33.0 cm.)
- Weight** - 20 lbs. (9.1 kg) (approx.)

ORDER THIS PRODUCT



Submarine Manufacturing & Products Limited

 +44 (0)1772 687775  info@smp-ltd.co.uk  www.smp-ltd.com
Blackpool Road, Newton, Preston, Lancashire, United Kingdom PR4 3RE

To order this product or to request a price contact our UK sales team on
+44 (0)1772 687775

Alternatively you can place a quote request through our website
<http://www.smp-ltd.co.uk> or send an email to sales@smp-ltd.co.uk